

COD. 498

Ideale per l'utilizzo professionale della raccolta di residui di lavorazione in concomitanza ad un utensile elettrico o pneumatico. Di facile utilizzo e praticità grazie ad un dispositivo elettronico che avvia automaticamente l'aspirapolvere.

This model has been studied to be used together with an electric or pneumatic tool for the professional suction of tailings. Practical and easy to use thanks to the simple use of a device which automatically switch the vacuum cleaner on when the tool is on.



AUTOMATIC STARTER



2 Motori
Motors



D Polvere
D Dry



W Acqua
W Wet



EA per utensile
elettrico e pneumatico
EA for electric tool
and pneumatic tool

COD. 420



COD. 498

Motors number	Numero motori	2
Stage	Stadi motori	double
Volt (V)	Volt (V)	220 - 240
Frequency (Hz)	Frequenza (Hz)	50 / 60
Cooling	Tipo raffreddamento	by pass
P max (W)	P max (W)	2600
P (W)	Potenza (W)	2300
P max tool (W)	P max utensile (W)	1200
Pressure min - max (bar)	Pressione mini - max (bar)	4 - 15
Waterlift (mm H ₂ O)	Depressione (mmH ₂ O)	2400
Air flow (m ³ /h)	Aria aspirata (m ³ /h)	430
Lpa sonorus 3mt (dB(A))	Lpa sonoro 3mt (dB(A))	67
Total tank capacity (lt)	Capacità tot. fusto (lt)	77 / 76
Weight (Kg)	Peso (Kg)	21,7 / 23,5

Standard Accessories and Filters

	DESCRIPTION	CODE
1	Flexible hose 3,3mt Ø28 complete	498.11
2	Polyester filter with ring Ø44	498.12
3	Nylon filter Ø440	498.13
4	Sponge filter for liquids	498.14

Options

Kit: KITW040 [5-6-7-8-9-10-11-12]

	DESCRIPTION	CODE
5	Crevice tool Ø40	498.15
6	Chrome extension wand Ø40	498.16
7	Chrome extension wand-male Ø40	498.17
8	Nozzle body A/P L400 Ø40	498.18
9	Slide-on for liquids nozzle L400	498.19
10	Slide-on brush for floor nozzle L400	498.20
11	Dusting brush Ø40	498.21
12	Complete flexible hose mt.2,5 Ø40	498.22
13	Paper bag 77lt Max 2mot	498.23
14	Polyester bag 77lt Max 2mot	498.24
15	Cartridge filter Ø250 - H178	498.25
16	Slide-on for carpet nozzle L400	498.26
17	Accessory basket L450 Exel-Bottom	498.27
18	Accessory basket L450 - Top	498.28
19	Exel black handle Ø25 - Complete	498.29
20	Flexible with pneumatic hose Ø28 4,5 mt	498.30
21	Y Coupling inlet	498.31

